



### Trulink<sup>®</sup> 4-Port VGA/USB 2.0 KVM Switch

- Supports video resolutions up to 2048 x 1536 pixels
- Supports Microsoft<sup>®</sup> Windows<sup>®</sup> (98, 98SE, 2000, ME<sup>®</sup>, XP, Vista,7), Mac<sup>®</sup> OS 9/X, Linux, and Sun<sup>®</sup> Micro OS
- Features autoscan and autoswitch
- Offers overcurrent protection
- Compatible with USB 2.0 specification Deep Color

## Specifications: Trulink® 4-Port VGA/USB 2.0 KVM Switch

### Signal Specifications:

---

Video Signal Supported:	VGA
Maximum Resolution Supported:	2048 x 1536
USB Specification Supported:	USB 2.0
Audio Signal Support (35568 only):	Stereo Audio
Switching Methods:	Keyboard Hotkeys Push button Auto-Scan

### Power Adapter Specifications

---

Power Input:	100-240V 50/60Hz, 0.4A
Power Output:	5V, 2.0A
Power Cable Length:	5ft
Power Pin Diameter:	5.5mm
Center Pin Polarity:	Positive

### Physical Characteristics:

---

Number of Computers Supported:	4
Computer Connection Ports:	HD15 (VGA) Male x 4 USB B Female x 4 3.5mm Female x 8 (35568 only)
Console Ports:	HD15 VGA Female x 1 USB A Female x 2 (keyboard and mouse) 3.5mm Female x 2 (35568 only)
USB Hub:	USB A Female x 2
Included Cables:	HD15 (VGA) M/F and USB A to B Combo Cable x 4 Dual 3.5mm cable x 2 (35568 only)
Cable Length:	1.8m
Housing Material:	Metal
Dimensions:	7.9 x 3.2 x 1.7in

Part Number	Description	Weight (lbs)
35567	Trulink® 4-Port VGA/USB 2.0 KVM Switch	5.224
35568	Trulink® 4-Port VGA/USB 2.0 KVM Switch with Audio	5.864