

SPECIFICATION SHEET



TruLink® 4 x 2 HDMI® Matrix Switch

- Supports 480i, 480p, 720p, 1080i and 1080p video resolutions
- Supports HDCP and DDWG standard for HDMI-compatible monitors
- Maximum cable distance: 15 meters (49 feet)
- TAA compliant
- One Year Warranty

Specifications: TruLink® 4 x 2 HDMI® Matrix Switch

Electrical Characteristics:

| | |
|---------------------------|-----------------------------------|
| Resolutions Supported: | 480i, 480p, 720p, 1080i and 1080p |
| Maximum Cable Distance: | 15m (49ft) |
| Specifications Supported: | HDCP, DDWG |

Power Adapter Specifications:

| | |
|----------------------|------------------------------|
| Power Input: | 100- 240VAC ~ 47-63Hz, 0.48A |
| Power Output:: | 5VDC 3.5A |
| Pin Diameter: | 5.5mm |
| Center Pin Polarity: | Positive |

Physical Characteristics:

| | |
|------------------------------|-------------------------------|
| Video Input Connectors: | HDMI Type A 19 pin Female x 4 |
| Video Output Connectors: | HDMI Type A 19 pin Female x 2 |
| Housing Material: | Metal |
| Operating Temperature Range: | 0° - 40°C (32° - 104°F) |
| Storage Temperature Range: | -20° - 60°C (20° - 140°F) |
| Dimensions: | 1.7 x 16.9 x 8.0 in |

Regulatory Approvals:

| | |
|---------------------|------------------------|
| Matrix Switch: | FCC, CE, RoHS |
| Power Adapter Only: | UL, CE, CSA, CEC, RoHS |

| Part Number | Description | Weight (lbs) |
|-------------|--------------------------------|--------------|
| 40011 | TruLink 4x2 HDMI Matrix Switch | 5.10 |



CABLES TO GO

Cables To Go
 3555 Kettering Blvd.
 Moraine, OH 45439
 Phone: 800.287.2843
 www.c2g.com

Follow Us

