



## TruLink® HDMI® Over Coax

- Supports a maximum video resolution of 1080i
- Supports a maximum cable length of 120m (390ft)
- Daisy-chain multiple receivers to support up to 24 monitors
- No software required
- Free technical support & 3yr warranty



# Specifications: TruLink® HDMI® Over Coax

## Video Signal Specifications:

Maximum Video Resolution Supported:	1080i
Maximum Cable Length Supported:	120m (390ft)

## Power Adapter\* Specifications:

Input Power:	100 - 240V~50/60Hz, 0.2A
Output Power:	5V, 1A
Cable Length:	5ft
Power Pin Diameter:	5.5mm
Center Pin Polarity:	Positive

\*A power adapter must be connected to each transmitter and receiver.

## Physical Characteristics:

### Transmitter

Video Input Connector:	HDMI Type A Female x2
Data Output Connector:	BNC Female Type 75Ω x2
LED Lights:	HDMI IN1 HDMI IN 2
Control:	Infrared (IR) Remote

### Receiver

Video Output Connector:	HDMI Type A Female
Data Input Connector:	BNC Female Type 75Ω
Data Output Connector:	BNC Female Type 75Ω
Operating Temperature Range:	0° - 50°C 15 - 80% Humidity, Non-Condensing
Storage Temperature Range:	-20° - 60°C 15 - 70% Humidity, Non-Condensing
Enclosure:	Metal
Dimensions (HWD):	117.5 x 68.0 x 26.5mm
Weight:	1.19lb
Approvals:	RoHS Compliant, CE, FCC
Package Type:	Box

Part Number	Description	Weight (lbs)
40574	TruLink® HDMI® over COAX Kit	1.19lb
40575	TruLink® HDMI® over COAX Receiver	0.85lb

