



### TruLink® Media Gateway Connectivity Panel w/iPod + Ethernet + Power Wall Mount - Standard Black - W3

The TruLink® Media Gateway by C2G® is a powerful all-in-one audio/video connectivity panel that enables users to easily and simply connect a wide array of consumer electronics devices to an HDTV. This active connectivity panel provides hassle-free connectivity for laptops, iPod® / iPad® / iPhone®, digital/video cameras, Blu-ray™ or DVD players and game consoles to HDTVs or projectors. The automatic switching functionality provides ease of use, while the USB port adds a convenient way to charge portable electronics. Designed to mount in-wall, in conference room tables, podiums, or other case goods, its versatility makes it a real problem solver for multiple applications in the corporate, education, healthcare and hospitality markets.

- Single HDMI output for all audio and video inputs
- Works with all HDTVs from 480i (NTSC)/576i (PAL) to 1080p
- Consumer Electronics Control (CEC) and RS232 serial support to control HDTVs, projectors and monitors
- Supports audio/video signals from iPod®/iPad®/iPhone® devices; Made for iPod/iPhone certified
- 6Amp combined circuit supports two AC outlets
- Connected device detection allows automatic switching between video inputs
- Charges portable electronic devices via the USB port (500mA)
- Three year warranty



# Specifications: TruLink® Media Gateway Connectivity Panel - W3

## Video Specifications:

---

HDMI features supported: 1080p resolution\*, CEC  
Maximum VGA resolution supported: 1280 x 1024

\*The HDMI input is supported at 1080p, the Composite Video input is upscaled to 1080p.

## Front Panel Connections:

---

Audio/Video inputs: HDMI, HD15(VGA), 3.5mm Stereo Audio, iPod, RCA Composite Video, RCA Stereo Audio  
Data port: RJ-45 - Ethernet  
Power output: USB-A\* female (500mA), 2 US universal AC outlets

\*The USB-A female port will support firmware updates via a USB flash drive.

## Rear Connections:

---

Audio/Video output: HDMI  
Data ports: RJ-45 - Ethernet  
RJ-25 - RS232 Serial  
Power: Screw terminals

## Approvals and Certifications:

---

Approvals and Certifications: FCC, ETL, CE, WEEE, RoHS

## Dimensions:

---

Housing dimensions (HxWxD): 2.95 x 12.40 x 2.95in (75.0 x 315.0 x 75.0mm)  
Cut-out dimensions\* (HxW): 2.3 x 11.9in (59.0 x 302.0mm)  
Weight: 3.91lbs

\*For in-wall mounting, allow a minimum of a 50.0mm (2.0in) space from a wall stud.

