



TruLink® Media Gateway Connectivity Panel w/iPod + Ethernet Furniture Mount - Standard Black - F2

The TruLink® Media Gateway by C2G® is a powerful all-in-one audio/video connectivity panel that enables users to easily and simply connect a wide array of consumer electronics devices to an HDTV. This active connectivity panel provides hassle-free connectivity for laptops, iPod® / iPad® / iPhone®, digital/video cameras, Blu-ray™ or DVD players and game consoles to HDTVs or projectors. The automatic switching functionality provides ease of use, while the USB port adds a convenient way to charge portable electronics. Designed to mount in/under conference room tables, podiums, or other case goods, its versatility makes it a real problem solver for multiple applications in the corporate, education, healthcare and hospitality markets.

- Single HDMI output for all audio and video inputs
- Works with all HDTVs from 480i (NTSC)/576i (PAL) to 1080p
- Consumer Electronics Control (CEC) and RS232 serial support to control HDTVs, projectors and monitors
- Supports audio/video signals from iPod®/iPad®/iPhone® devices; Made for iPod/iPhone certified
- Connected device detection allows automatic switching between video inputs
- Charges portable electronic devices via the USB port (500mA)
- Three year warranty



Specifications: TruLink® Media Gateway Connectivity Panel - F2

Video Specifications:

HDMI features supported: 1080p resolution*, CEC
Maximum VGA resolution supported: 1280 x 1024

*The HDMI input is supported at 1080p, the Composite Video input is upscaled to 1080p.

Front Panel Connections:

Audio/Video inputs: HDMI, HD15(VGA), 3.5mm Stereo Audio, iPod, RCA Composite Video, RCA Stereo Audio
Data port: RJ-45 - Ethernet
Power output: USB-A* female (500mA)

*The USB-A female port will support firmware updates via a USB flash drive.

Rear Connections:

Audio/Video output: HDMI
Data ports: RJ-45 - Ethernet
RJ-25 - RS232 Serial
Power: 5.5mm DC

Power Adapter Specifications:

Power input: 100-240V ~ 50/60Hz, 0.8A
Power output: 5V, 3A
Cable Length: 6ft
DC power pin diameter: 5.5mm
Center pin polarity: Positive

Approvals and Certifications:

Approvals and Certifications: FCC, ETL, CE, WEEE, RoHS

Dimensions:

Housing dimensions (HxWxD): 2.95 x 7.67 x 2.44in (75.0 x 195.0 x 62.0mm)
Cut-out dimensions* (HxW): 2.30 x 7.20in (59.0 x 182.0mm)
Weight: 2.71lbs

*For in-furniture mounting, allow a minimum of a 50.0mm (2.0in) space from any internal support or brace.

