



RapidRun[®] Single Gang Integrated Wall Plate HD15 + 3.5mm + Keystone Wall Plate

- Color Code: Yellow (for use with PC runners)
- Supports resolutions up to 1600 x 1200 pixels (UXGA resolution)
- Three 28AWG coaxial cables with braided copper shielding, three 24AWG twisted pair, and a single 24AWG pair
- Fits into most single gang J-boxes.
- Lifetime Warranty

*The specifications apply only to the raw cable used to construct the cable assemblies

Specifications: RapidRun® Single Gang Integrated Wall Plate HD15 + 3.5mm + Keystone Wall Plate

Electrical Characteristics:

3 Coax Conductors:

Impedance:	75 ± 50hm		
Capacitance:	71 ± 2pF/ ft nom		
Velocity of Propagation:	78 ± 1%		
DC Resistance:	237 ± 10Ω/km		
Dielectric Strength:	500VAC/1 minute min.		
Insulation Resistance (500V):	10MΩ/KM		
Attenuation (dB/6m):	Red Coax	Green Coax	Blue Coax
	1MHz	0.1464	0.1376
	10MHz	0.86	0.97
	100MHz	2.98	3.23
	200MHz	4.45	4.87
	500MHz	6.72	7.75
	700MHz	9.95	12.01
	1000MHz	13.20	17.52

3 Twisted Pair Conductors

DC Resistance:	93.25Ω/m at 20°C
Dielectric Strength:	750VAC/ minute min.
Insulation Resistance:	100Mohm/KM at 20°C

Physical Characteristics:

Voltage Rating:	30V
Temperature Rating:	80°C
Temperature Range:	-25° ~ 80°C
Minimum Bend Radius:	90mm
Approvals:	RoHS Compliant
Warranty:	Lifetime
Package Type:	Box

Item	Description	Weight (lbs)
42326	RapidRun Single Gang Integrated Wall Plate HD15 + 3.5mm + Keystone Wall Plate	0.34

Specifications: RapidRun® Single Gang Integrated Wall Plate HD15 + 3.5mm + Keystone Wall Plate

Conductor (Qty. 3):

Conductor Type:	28AWG 7/0.127 Tinned Copper
Dielectric:	Minimum Avg. Thickness: 1.57 mm Foam PE
Shield:	Spiral 90% Coverage Tinned Copper
Insulation:	Minimum Avg. Thickness: 0.23 mm PVC: (1) red, (1) blue, (1) green

Conductor (Qty. 3 twisted pair + 2 conductors):

Conductor Type:	24AWG 7/0.2 Tinned Copper
Insulation:	Minimum Avg. Thickness: 0.23 mm PVC

HD15 Connector (Qty. 1):

Connector Type:	High Density D-Sub 15 pin
Gender:	Female
Contact Material:	Brass, 3µm Gold Plating
Insulation:	Black PBT

Note: Pin 9 is not loaded.

3.5mm Connector (Qty. 1):

Connector Type:	3.5mm Stereo
Gender:	Female
Contact Material:	Brass, 3µm Nickel Plating

RapidRun Din Connector (Qty. 1):

Connector Type:	DIN 15 pin
Gender:	Male
Contact Material:	Brass, 3µm Gold Plating
Insulation:	Black PBT

Overall Cable

Jacket: Yellow Heat Shrink

