



## RapidRun<sup>®</sup> Single Gang (2) XLR - Brushed Aluminum

- Color Code: Yellow (for use with PC runners)
- Supports transmission of two balanced audio signal
- Six 24AWG conductors
- Fits into most single gang J-boxes.
- Lifetime Warranty

\*The specifications apply only to the raw cable used to construct the cable assemblies

# Specifications: RapidRun® Single Gang (2) XLR - Brushed Aluminum

## Electrical Characteristics:

### 6 Conductors

DC Resistance:	93.25Ω/m at 20°C
Dielectric Strength:	750VAC/ minute min.
Insulation Resistance:	100Mohm/KM at 20°C

## Physical Characteristics:

Voltage Rating:	30V
Temperature Rating:	80°C
Temperature Range:	-25° ~ 80°C
Minimum Bend Radius:	90mm

Approvals:	RoHS Compliant
Warranty:	Lifetime
Package Type:	Box

Item	Description	Weight (lbs)
42340	RapidRun Single Gang (2) XLR - Brushed Aluminum	0.39

### Conductor (Qty. 6 conductors):

Conductor Type:	24AWG 7/0.2 Tinned Copper
Insulation	Minimum Avg. Thickness: 0.23 mm PVC: (1) black, (1) brown, (1) red, (1) orange, (1) yellow, (1) green

### XLR Connector (Qty. 2):

Connector Type:	3-pin XLR Connector
Gender:	Female
Contact Material:	Brass, 3µm Silver Plating

### RapidRun Din Connector (Qty. 1):

Connector Type:	DIN 15 pin
Gender:	Male
Contact Material:	Brass, 3µm Gold Plating
Insulation:	Black PBT

### Overall Cable:

Jacket:	Yellow Heat Shrink
---------	--------------------

