



RapidRun® Digital HDMI® Active Wall Plate

- Color Code: Red (for use with Digital runners)
- Supports HDMI high resolution video up to 1080p
- Uses four 24 AWG shielded twisted pairs with drain wire, one 24 AWG twisted pair, and five 24 AWG conductors
- Fits into most J-boxes.
- Compatible with Leviton Decora® brand cover plates
- Lifetime Warranty

*The specifications apply only to the raw cable used to construct the cable assemblies

Note: Decora® is a registered trademark of Leviton Manufacturing Company, Inc. This product is not manufactured or endorsed by the Leviton Manufacturing Company, Inc



Specifications: RapidRun® Digital HDMI® Active Wall Plate

Electrical Characteristics:

Impedance:	100 ± 10 Ω		
DC Resistance:	DC300V		
Velocity of Propagation (nom.):	78 ± 1%		
Insulation Resistance (500V):	93.25Ω/KM at 20°C max.		
Attenuation (nom.):	Frequency	Min Limit	Max Limit
	1 ~ 825 MHz	-5 dB	-5 dB
	825 ~ 2475 MHz	-5 dB	-12 dB
	2475 ~ 4125 MHz	-12 dB	- 20 dB
	4125 ~ 5100 MHz	-20 dB	-25 dB

Physical Characteristics:

Voltage Rating:	30V
Temperature Rating:	75°C
Operating Temperature Range:	-40° C ~ 75°C
Minimum Bend Radius	90 mm
Approvals:	RoHS Compliant
Warranty:	Lifetime
Package Type:	Box

Item	Description	Weight
42422	RapidRun Digital HDMI Active Wall Plate - White	0.36
42423	RapidRun Digital HDMI Active Wall Plate - Ivory	0.36
42434	RapidRun Digital HDMI Active Wall Plate - Black	0.36



Specifications: RapidRun® Digital HDMI® Active Wall Plate

Conductor 1 (1 pair & 5 conductors):

Conductor Type: 24AWG (7/0.20)
Tinned Copper

Insulation: Minimum Avg. Thickness: 0.4mm
HD-PE I.D.: 1.3 ± 0.05 mm
(1 pair) yellow & orange,
(1) purple, (1) gray, (1) pink,
(1) red, (1) white

Conductor 2 (4 pair):

Conductor Type: 28AWG (7/0.20)
Silver Plated Copper

Insulation: Minimum Avg. Thickness: 0.4mm
FM-PE+SKIN
I.D.: 1.55 ± 0.05 mm
(1)white & brown, (1)white & red,
(1)white & green, (1)white & blue

Shield: Aluminum Mylar wrap 100%
Mylar 100%

Drain Wire: 24AWG (7/.20) Tinned Copper

Overall Cable:

AL Mylar Shield:
Braided Shield:
Drain Wire:
Jacket:

HDMI Connector:

Connector Type: HDMI Type A
Gender: Female
Contact Material: Brass, 15 μ m Gold Plating
Insulation: Black PBT

RapidRun Din Connector :

Connector Type: 19 pin Din
Gender: Male
Contact Material: Brass, 15 μ Gold Plating
Insulation: Black PBT

100% Coverage
85% Coverage (24/12/0.10 TC)
24AWG (7/0.20 TC)
PVC – CL2 rated
Minimum Avg. Thickness: 0.51 mm (min.)
O.D.: 10.5 ± 0.15 mm
Red Heat Shrink

