



### **RapidRun® Dual Din 15 + 15 Wall Plate**

- Color Code: Yellow (for use with PC runners)
- Supports resolutions up to 1600 x 1200 pixels (UXGA resolution)
- Three 28AWG coaxial cables with braided copper shielding, three 24AWG twisted pair, and a single 24AWG pair
- Fits into most J-boxes.
- Compatible with Leviton Decora® brand cover plates
- Lifetime Warranty

\*The specifications apply only to the raw cable used to construct the cable assemblies

Note: Decora® is a registered trademark of Leviton Manufacturing Company, Inc. This product is not manufactured or endorsed by the Leviton Manufacturing Company, Inc.

---

3555 Kettering Blvd. | Moraine OH | 45439 | [www.cablestogo.com](http://www.cablestogo.com) | 800.287.2843

## Specifications: RapidRun® Dual Din 15 + 15 Wall Plate

### Electrical Characteristics:

Impedance:	75 ± 5 Ohm
Capacitance:	71 ± 2 pF/ ft nom
Velocity of Propagation:	78 ± 1%
DC Resistance:	237 ± 10 Ω/km
Dielectric Strength:	500VAC/1 minute min.
Insulation Resistance (500V):	10 MΩ/KM
Attenuation (dB/6m):	

	Red Coax	Green Coax	Blue Coax
1 MHz	0.1464	0.1376	0.1419
10 MHz	0.86	0.97	0.4058
100 MHz	2.98	3.23	1.259
200 MHz	4.45	4.87	1.823
500 MHz	6.72	7.75	3.0028
700 MHz	9.95	12.01	3.64
1000 MHz	13.20	17.52	4.5923
500 MHz	6.72	7.75	3.0028
700 MHz	9.95	12.01	3.64
1000 MHz	13.20	17.52	4.5923

### 3 Twisted Pairs + 2 Conductors

DC Resistance:	93.25 Ω/m at 20°C
Dielectric Strength:	750VAC/ 1 minute min.
Insulation Resistance:	100 Mohm/KM at 20°C

### Physical Characteristics:

Voltage Rating:	30V
Temperature Rating:	80°C
Temperature Range:	-25° ~ 80° C

Approvals:	RoHS Compliant
Warranty:	Lifetime
Package Type:	Polybag

Item	Description	Weight (lbs)
42109	RapidRun Dual Din 15 + 15 pin Wall Plate – White	0.42
42110	RapidRun Dual Din 15 + 15 pin Wall Plate – Ivory	0.42
42131	RapidRun Dual Din 15 + 15 pin Wall Plate – Black	0.42

## Specifications: RapidRun® Dual Din 15 + 15 Wall Plate

### Conductor (Qty. 3):

Conductor Type:	28AWG 7/0.127 Tinned Copper
Dielectric:	Minimum Avg. Thickness: 1.57mm Foam PE
Shield:	Spiral 90% Coverage Tinned Copper
Insulation:	Minimum Avg. Thickness: 0.23mm PVC: (1) red, (1) blue, (1) green

### Conductor (Qty. 3 twisted pair + 2 conductors):

Conductor Type:	24AWG 7/0.2 Tinned Copper
Insulation:	Minimum Avg. Thickness: 0.23mm PVC

### RapidRun Din Connector (Qty. 2):

Connector Type:	DIN 15 - pin
Gender:	Female
Contact Material:	Brass, 3µm Gold Plating
Insulation:	Black PBT

### RapidRun Din Connector (Qty. 1):

Connector Type:	DIN 12 - pin
Gender:	Male
Contact Material:	Brass, 3µm Gold Plating
Insulation:	Black PBT

### Overall Cable

Jacket:	Yellow Heat Shrink
---------	--------------------

