



RapidRun[®] Double Gang Integrated HD15 + 3.5mm + RCA Audio/Video + (2) Keystone Wall Plate

- Color Code: Yellow (for use with PC runners)
- Supports resolutions up to 1600 x 1200 pixels (UXGA resolution)
- Three 28AWG coaxial cables with braided copper shielding, three 24AWG twisted pair, and a single 24AWG pair
- Fits into most J-boxes.
- Lifetime Warranty

*The specifications apply only to the raw cable used to construct the cable assemblies

Specifications: RapidRun® Double Gang Integrated HD15 + 3.5mm + RCA Audio/Video + (2) Keystone Wall Plate

Electrical Characteristics:

3 Coax Conductors:

Impedance:	75 ± 5Ohm		
Capacitance:	71 ± 2pF/ ft nom		
Velocity of Propagation:	78 ± 1%		
DC Resistance:	237 ± 10Ω/km		
Dielectric Strength:	500VAC/1 minute min.		
Insulation Resistance (500V):	10MΩ/KM		
Attenuation (dB/6m):	Red Coax	Green Coax	Blue Coax
1MHz	0.1464	0.1376	0.1419
10MHz	0.86	0.97	0.4058
100MHz	2.98	3.23	1.259
200MHz	4.45	4.87	1.823
500MHz	6.72	7.75	3.0028
700MHz	9.95	12.01	3.64
1000MHz	13.20	17.52	4.5923

3 Twisted Pair Conductors

DC Resistance:	93.25Ω/m at 20°C
Dielectric Strength:	750VAC/ minute min.
Insulation Resistance:	100Mohm/KM at 20°C

Physical Characteristics:

Voltage Rating:	30V
Temperature Rating:	80°C
Temperature Range:	-25° ~ 80°C
Minimum Bend Radius:	90mm
Approvals:	RoHS Compliant
Warranty:	Lifetime
Package Type:	Box

Item	Description	Weight (lbs)
42311	RapidRun Double Gang Integrated HD15 + 3.5mm + RCA Audio/Video + (2) Keystone Wall Plate - Brushed Aluminum	0.48
42330	RapidRun Double Gang Integrated HD15 + 3.5mm + RCA Audio/Video + (2) Keystone Wall Plate - White	0.48
42331	RapidRun Double Gang Integrated HD15 + 3.5mm + RCA Audio/Video + (2) Keystone Wall Plate - Black	0.48

Specifications: RapidRun® Double Gang Integrated HD15 + 3.5mm + RCA Audio/Video + (2) Keystone Wall Plate

Conductor (Qty. 3):

Conductor Type:	28AWG 7/0.127 Tinned Copper
Dielectric:	Minimum Avg. Thickness: 1.57mm Foam PE
Shield:	Spiral 90% Coverage Tinned Copper
Insulation:	Minimum Avg. Thickness: 0.23mm PVC: (1) red, (1) blue, (1) green

Conductor (Qty. 3 twisted pair + 2 conductors):

Conductor Type:	24AWG 7/0.2 Tinned Copper
Insulation:	Minimum Avg. Thickness: 0.23mm PVC

HD15 Connector (Qty. 1):

Connector Type:	High Density D-Sub 15 pin
Gender:	Female
Contact Material:	Brass, 3µm Gold Plating
Insulation:	Black PBT

Note: Pin 9 is not loaded.

3.5mm Connector (Qty. 1):

Connector Type:	3.5mm Stereo
Gender:	Female
Contact Material:	Brass, 3µm Nickel Plating

RCA Connector (Qty. 3):

Connector Type:	RCA
Gender:	Female
Contact Material:	Brass, 3µm Nickel Plating
Insulation:	Yellow, Red, and White PBT

RapidRun Din Connector (Qty. 1):

Connector Type:	DIN 15 pin
Gender:	Male
Contact Material:	Brass, 3µm Gold Plating
Insulation:	Black PBT

Overall Cable

Jacket:	Yellow Heat Shrink
---------	--------------------

