



RapidRun® XLR (Female) Balanced Audio Flying Lead

- Color Code: Yellow (for use with PC runners)
- Supports transmission two XLR balanced audio signals
- Two 22AWG shielded pairs
- Fully molded connectors provide excellent strain relief
- Lifetime Warranty

*The specifications apply only to the raw cable used to construct the cable assemblies

Specifications: RapidRun® XLR (Female) Balanced Audio Flying Lead

Electrical Characteristics:

Conductors:

Impedance:	50 ± 5Ohm
Capacitance:	52pF/m (16pF/ft)
DC Resistance:	0.056Ohm/m (0.017Ohm/ft)
Dielectric Strength:	500VDC/15 seconds min.
Insulation Resistance (500V):	100 MOhm min at 500V
Attenuation (dB/50ft):	
	90MHz 4.212
	220MHz 7.131
	470MHz 11.784
	770MHz 17.617

Physical Characteristics:

Voltage Rating:	30V
Temperature Rating:	70°C
Temperature Range:	-20° ~ 70° C
Minimum Bend Radius:	25.5mm
Approvals:	RoHS Compliant
Warranty:	Lifetime
Package Type:	Polybag

Item	Description	Weight (lbs)
42343	6ft RapidRun XLR (Female) Balanced Audio Flying Lead	0.50

Specifications: RapidRun® XLR (Female) Balanced Audio Flying Lead

Conductor (Qty. 2):

Conductor Type: 22 AWG 29/0.12
Bare Copper
Insulation: FPE
(1) red, (1) white

XLR Connector (Qty. 1):

Connector Type: 3-Pin XLR
Gender: Female
Contact Material: Brass, 3µm Silver Plating

RapidRun Din Connector (Qty. 1):

Connector Type: DIN 15 pin
Gender: Male
Contact Material: Brass, 3µm Gold Plating
Insulation: Black PBT

Overall Cable:

Shield: Aluminum Mylar Wrap – 100%
Braided Shield 16/7/0.12 - 85% Coverage -
Bare Copper
Jacket: PVC
Yellow Heat Shrink

