



### **RapidRun® XLR (Male) Balanced Audio Flying Lead**

- Color Code: Yellow (for use with PC runners)
- Supports transmission two XLR balanced audio signals
- Two 22AWG shielded pairs
- Fully molded connectors provide excellent strain relief
- Lifetime Warranty

\*The specifications apply only to the raw cable used to construct the cable assemblies

## Specifications: RapidRun® XLR (Male) Balanced Audio Flying Lead

### Electrical Characteristics:

---

#### Conductors:

Impedance:	50 ± 5Ohm
Capacitance:	52pF/m (16pF/ft)
DC Resistance:	0.056Ohm/m (0.017Ohm/ft)
Dielectric Strength:	500VDC/15 seconds min.
Insulation Resistance (500V):	100 MOhm min at 500V
Attenuation (dB/50ft):	
	90MHz            4.212
	220MHz           7.131
	470MHz           11.784
	770MHz           17.617

### Physical Characteristics:

---

Voltage Rating:	30V
Temperature Rating:	70°C
Temperature Range:	-20° ~ 70° C
Minimum Bend Radius:	25.5mm
Approvals:	RoHS Compliant
Warranty:	Lifetime
Package Type:	Polybag

Item	Description	Weight (lbs)
42349	6ft RapidRun (2) XLR (Male) Balanced Audio Flying Lead	0.50

## Specifications: RapidRun® XLR (Male) Balanced Audio Flying Lead

### Conductor (Qty. 2):

Conductor Type: 22 AWG 29/0.12  
Bare Copper  
Insulation: FPE  
(1) red, (1) white

### XLR Connector (Qty. 1):

Connector Type: 3-Pin XLR  
Gender: Male  
Contact Material: Brass, 3µm Silver Plating

### RapidRun Din Connector (Qty. 1):

Connector Type: DIN 15 pin  
Gender: Male  
Contact Material: Brass, 3µm Gold Plating  
Insulation: Black PBT

### Overall Cable:

Shield: Aluminum Mylar Wrap – 100%  
Braided Shield 16/7/0.12 - 85% Coverage -  
Bare Copper  
Jacket: PVC  
Yellow Heat Shrink

