



RapidRun® Double Gang VGA (HD15) + 3.5mm + HDMI Pass Through Wall Plate

- Color Code: Orange (for use with Multi-Format runners)
- Supports resolutions up to 1600 x 1200 pixels (UXGA resolution)
- Supports resolutions up to 1080p (HDMI Pass Through)
- Three 28 AWG coaxial cables with braided copper shielding, three 26 AWG twisted pair, and a single 26 AWG pair
- Fits into most J-boxes.
- Lifetime Warranty



Specifications: RapidRun® Double Gang VGA (HD15) + 3.5mm + HDMI Pass Through Wall Plate

Electrical Characteristics:

Impedance:	75 ± 5 Ohm		
Capacitance:	71 ± 2 pF/ ft nom		
Velocity of Propagation	78 ± 1%		
DC Resistance:	237 ± 10 Ω/km		
Dielectric Strength:	500VAC/1 minute min		
Insulation Resistance:	93.25 Ω/KM at 20°C max.		
Attenuation (nom.):		Min	Max
		Limit	Limit
	Frequency		
	1~825 MHz	-5 dB	-5 dB
	825~2475 MHz	-5 dB	-12 dB
	2475~4125 MHz	-12 dB	-20 dB
	4125~5100 MHz	-20 dB	-25 dB

Physical Characteristics:

Voltage Rating:	30V
Temperature Rating:	80°C
Temperature Range:	-25° ~ 80° C
Approvals:	CE
Warranty:	Lifetime
Package Type:	Box

Conductor (Qty 3):

Conductor Type:	24 AWG (7/0.2) Tinned Copper
Insulation:	Min Avg. Thickness: 1.57 mm Foam PE Min Avg. Thickness: 0.23mm PVC: (1) red, (1) blue, (1) green
Shield	Spiral 90% Coverage Tinned Copper

Conductor (Qty 3 twisted pair + 2 conductors):

Conductor Type:	24 AWG (7/0.2) Tinned Copper
Insulation:	Min Avg. Thickness: 0.23 mm PVC

HD15 Connector (Qty. 1):

Connector Type:	High Density D-Sub 15 pin
Gender:	Female
Contact Material:	Brass, 3 µm Gold Plating
Insulation:	Black PBT

3.5mm Connector (Qty. 1):

Connector Type:	3.5mm Stereo
Gender:	Female
Contact Material:	Brass, 3 µm Nickel Plating

RapidRun Connector (Qty. 1):


Connector Type:	DIN 15 pin
Gender:	Male
Contact Material:	Brass, 3 µm Gold Plating
Insulation	Black PBT

HDMI Connector (Qty 1):

Connector Type:	HDMI 19pin
Gender:	Female



Specifications: RapidRun® Double Gang VGA (HD15) + 3.5mm + HDMI Pass Through Wall Plate



Part Number	Description	Weight (lbs)
60017	RapidRun® Double Gang VGA (HD15) + 3.5mm + HDMI Pass Through Wall Plate	

