


For fast Ethernet networks that require bandwidth-intensive voice, data, or video distribution applications. Meets all Cat5e TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code your network installation.



Features & Benefits

Designed for network adapters, hubs, switches, routers and more

Constructed with unshielded twisted pair wires

Available in 10 colors to color-code a network

Available in lengths up to 150ft

CMG In-Wall Rated Jacket

Specifications

General Info

Product Line	C2G	Replaced by Part Number	04199
Color	Orange	UPC Number	757120005742
Country Of Origin	China	Application Sector	Commercial, Industrial, Residential
Type	Cable		

Dimensions

Cable Length	10 ft	Outside Diameter	5.3 mm
--------------	-------	------------------	--------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Category Performance Rating	Cat 5e
Wire Gauge	24 AWG	Shielded/Unshielded	Unshielded
Conductor	4-Pair Twisted	Shield Type	UTP
Cable Type	Ethernet Patch Cable	Jacket Rating	Standard / Non-Rated

Cable Diameter	5.3 mm	Connector Type	Non-booted
Indoor/Outdoor	Indoor	Connector 2	RJ-45 Male
Connector 1	RJ-45 Male		
