



This OM3 Duplex Multimode Fiber Optic Cable is ideal for connecting 10GBase-SR, 10GBase-LRM, SFP+ and QSFP+ transceivers for 10 gigabit network connections. This cable provides backward compatibility with existing 50/125 equipment and the performance headroom required to support LED and VCSEL laser light sources, and 10 gigabit ethernet applications.

## Features & Benefits

Designed for 10Gbase-SR and LRM applications

Backward compatible with existing 50/125 equipment

Available in SC, ST and LC connectors

Available in lengths up to 10m

## Specifications

### General Info

|                    |                        |                   |           |
|--------------------|------------------------|-------------------|-----------|
| Product Line       | C2G                    | Color             | Aqua      |
| UPC Number         | 757120011248           | Country Of Origin | Hong Kong |
| Application Sector | Commercial, Industrial | Type              | Cable     |

### Dimensions

|              |         |
|--------------|---------|
| Cable Length | 13.1 ft |
|--------------|---------|

### Additional Information

|                          |     |                          |                              |
|--------------------------|-----|--------------------------|------------------------------|
| Prop 65 Warning Required | Yes | Prop 65 Warning Language | Cancer and Reproductive Harm |
|--------------------------|-----|--------------------------|------------------------------|

### Technical Information

|             |                |                 |                          |
|-------------|----------------|-----------------|--------------------------|
| Cable Type  | Multimode, OM3 | Jacket Material | PVC (Polyvinyl Chloride) |
| Bend Radius | 50 mm          | Simplex/Duplex  | Duplex                   |
| Cable Type  | Fiber Optic    | Jacket Rating   | Riser OFNR-Rated         |

---

Data Transfer Rate

10 Gbps

Adapter Rear

SC Male, SC Male

---

Adapter Front

LC Male, LC Male

Fiber Size

50/125

---