



This OM4 Duplex Multimode Fiber Optic Cable is ideal for connecting 40GBase BiDi 10GBaseSR, SFP+ and QSFP+ transceivers for 40 and 10 Gigabit network connections. This cable provides backward compatibility with existing 50/125 equipment and the performance headroom required to support LED and VCSEL laser light sources, and 40 or 10 gigabit Ethernet applications in a datacenter or wiring closet..

## Features & Benefits

- Constructed to support OM4 transmission standards
- Support for 10 Gigabit and 40 Gigabit Ethernet communication
- Multimode fiber construction - 50/125 diameter core and cladding

## Specifications

### General Info

|                    |                        |                   |           |
|--------------------|------------------------|-------------------|-----------|
| Product Line       | C2G                    | Color             | Aqua      |
| UPC Number         | 757120011477           | Country Of Origin | Hong Kong |
| Application Sector | Commercial, Industrial | Type              | Cable     |

### Dimensions

|              |         |
|--------------|---------|
| Cable Length | 26.2 ft |
|--------------|---------|

### Additional Information

|                          |     |                          |                              |
|--------------------------|-----|--------------------------|------------------------------|
| Prop 65 Warning Required | Yes | Prop 65 Warning Language | Cancer and Reproductive Harm |
|--------------------------|-----|--------------------------|------------------------------|

### Technical Information

|            |                |                 |                          |
|------------|----------------|-----------------|--------------------------|
| Cable Type | Multimode, OM4 | Jacket Material | PVC (Polyvinyl Chloride) |
|------------|----------------|-----------------|--------------------------|

---

|                    |                  |                |                  |
|--------------------|------------------|----------------|------------------|
| Bend Radius        | 10 mm            | Simplex/Duplex | Duplex           |
| Cable Type         | Fiber Optic      | Jacket Rating  | Riser OFNR-Rated |
| Data Transfer Rate | 40 Gbps          | Adapter Rear   | SC Male, SC Male |
| Adapter Front      | LC Male, LC Male | Fiber Size     | 50/125           |

---