



Why run all new cables for RS-232 control of your audio/video system, when you can use this easy adapter? The Velocity RS-232 adapter leverages your DB9 or 3.5mm stereo audio cable to run 3-conductor RS-232 control signals between your control unit and your video display. Fully molded DB9 and 3.5mm connectors provide excellent strain relief. This adapter is ideal for use with computers, projectors, and any control unit/display requiring 3-conductor RS-232 serial control.

Please Note: Not all serial control methods are supported by this adapter. This product is intended only for use with 3-wire RS-232 control cables with common ground (pin 5), transmit data (pin 3), and receive data (pin 2). For the exact pinout of your audio/video equipment, please contact your RapidRun sales representative for assistance, or call customer service at 1-800-506-9607.

## Features & Benefits

- Adapts a DB9 connection to a 3.5mm connection
- Fully molded DB9 and 3.5mm connectors provide excellent strain relief
- Allows for 3-conductor RS-232 control signals between your control unit and your video display

## Specifications

### General Info

Product Line	C2G	UPC Number	757120024453
Country Of Origin	Vietnam	Application Sector	Residential, Commercial, Industrial
Type	Cable, Adapter		

### Dimensions

Cable Length	1.5 ft
--------------	--------

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

### Technical Information

---

Jacket Material	PVC (Polyvinyl Chloride)	Cable Type	Adapter
Jacket Rating	Standard Non-Rated	Adapter Rear	3.5mm Stereo Male
Adapter Front	DB9 Female		

---