



Our line of null modem serial cables allows two DTE or DCE devices to communicate with no conflict in data transmission. The transmit and receive signals are crossed to ensure proper data transmission. Each null modem cable is designed with a rugged, overmolded construction that provides added strain relief and a solid connection each time.

Plus the cable is foil shielded for EMI/RFI protection from surrounding office equipment and fluorescent lights. Thumbscrew connectors provide a fast, easy connection every time.

## Features & Benefits

Null-modem wiring scheme

Fully molded connector and strain relief

Shielded to protect from interference

## Specifications

### General Info

Product Line	C2G	Color	Beige
UPC Number	757120030454	Country Of Origin	Vietnam
Features	RS232	Application Sector	Residential, Commercial, Industrial
Warranty Type	Lifetime	Type	Cable

### Dimensions

Product Length US	10.0 FT	Cable Length	10 ft
-------------------	---------	--------------	-------

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

### Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Cable Type	Serial, Null Modem
-----------------	--------------------------	------------	--------------------

---

Jacket Rating

Standard / Non-Rated

Adapter Rear

DB9 Female

---

Adapter Front

DB9 Female

---