C2G

# 2ft (0.6m) Cat6 Non-Booted Unshielded (UTP) Ethernet Network Patch Cable - Blue

Part No. CG-04086

For fast Ethernet and Gigabit computer networks that require bandwidth-intensive voice, data, or video distribution applications. Meets all Cat6 TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code your network installation.

## Features & Benefits

- Designed for network adapters, hubs, switches, routers, HDBaseT applications and more
- Supports 10 Gigabit networks up to 180ft for fast data transmission and maximum performance and supports 1 Gigabit up to 328ft
- Meets all Cat6 TIA/EIA requirements for supporting a wide variety of applications
- Constructed with unshielded twisted pair (UTP) wires, designed to counter EMI, RFI, and crosstalk
- Available in a variety of colors to color-code a network

## Specifications

### General Info

| | | | |
|---|---|---|---|
| Product Line | C2G | Color | Blue |
| UPC Number | 757120040866 | Country Of Origin | Vietnam |
| Features | PoE (Power Over Ethernet) | Application Sector | Commercial, Industrial, Residential |
| Warranty Type | Lifetime | Type | Cable |

### Dimensions

| | | | |
|---|---|---|---|
| Product Length US | 2.0 FT | Cable Length | 2 ft |

### Technical Information

| | | | |
|---|---|---|---|
| Jacket Material | PVC (Polyvinyl Chloride) | Wire Gauge | 24 AWG |

| | | | |
|---|---|---|---|
| Cable Type | Ethernet Patch Cable, Unbooted, Unshielded (UTP) | Jacket Rating | Standard / Non-Rated |
| Cable Diameter | 6 mm | Adapter Rear | RJ-45 Male |
| Adapter Front | RJ-45 Male | | |