

For fast Ethernet and Gigabit computer networks that require bandwidth-intensive voice, data, or video distribution applications. Meets all Cat6 TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code your network installation.



Features & Benefits

| Designed for network adapters, hubs, switches, routers, HDBaseT applications and more | Supports 10 Gigabit networks up to 180ft for fast data transmission and maximum performance and supports 1 Gigabit up to 328ft |
|---|--|
| Meets all Cat6 TIA/EIA requirements for supporting a wide variety of applications | Constructed with unshielded twisted pair (UTP) wires, designed to counter EMI, RFI, and crosstalk |

Available in a variety of colors to color-code a network

Specifications

General Info

| Product Line | C2G | Replaced by Part Number | 04241 | | | |
|---------------------------------------|-------------------------------------|-------------------------|---------------------------|--|--|--|
| Color | White | UPC Number | 757120042402 | | | |
| Country Of Origin | China | Features | PoE (Power Over Ethernet) | | | |
| Application Sector | Commercial, Industrial, Residential | Туре | Cable | | | |
| Dimensions | | | | | | |
| Product Length US | 9.0 FT | Cable Length | 9 ft | | | |
| Listing Agencies / 3rd Party Agencies | | | | | | |
| CE Certified | Yes | REACH Compliant | Yes | | | |
| Additional Information | | | | | | |
| RoHS Compliant | Yes | | | | | |
| Technical Information | | | | | | |
| | | | | | | |

| Jacket Material | PVC (Polyvinyl Chloride) | Category Performance Rating | Cat 6 |
|-----------------|--------------------------|-----------------------------|----------------------|
| Wire Gauge | 24 AWG | Shielded/Unshielded | Unshielded |
| Shield Type | UTP | Cable Type | Ethernet Patch Cable |
| Jacket Rating | Standard / Non-Rated | Cable Diameter | 6 mm |
| Connector Type | Non-booted | Indoor/Outdoor | Indoor |
| Connector 2 | RJ-45 Male | Connector 1 | RJ-45 Male |