

## $\begin{tabular}{ll} $C2G$ & 12ft (3.7m) Cat6 Non-Booted Unshielded (UTP) Ethernet Network Patch Cable - White Part No. CG-04242 & \end{tabular}$



For fast Ethernet and Gigabit computer networks that require bandwidth-intensive voice, data, or video distribution applications. Meets all Cat6 TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code your network installation.

## Features & Benefits

Designed for network adapters, hubs, switches, routers, HDBaseT applications and more

Meets all Cat6 TIA/EIA requirements for supporting a wide variety of applications

Available in a variety of colors to color-code a network

Supports 10 Gigabit networks up to 180ft for fast data transmission and maximum performance and supports 1 Gigabit up to 328ft

Constructed with unshielded twisted pair (UTP) wires, designed to counter EMI, RFI, and crosstalk

## **Specifications**

General Info			
Product Line	C2G	Replaced by Part Number	CG-04095, CG-04039
Color	White	UPC Number	757120042426
Country Of Origin	Vietnam	Features	PoE (Power Over Ethernet)
Application Sector	Commercial, Industrial, Residential	Warranty Type	Lifetime
Туре	Cable		
Dimensions			
Product Length US	12.0 FT	Cable Length	12 ft

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	24 AWG
Cable Type	Ethernet Patch Cable, Unbooted, Unshielded (UTP)	Jacket Rating	Standard / Non-Rated
Cable Diameter	6 mm	Adapter Rear	RJ-45 Male
Adapter Front	RJ-45 Male		