



Mini-SAS four lane, passive twinaxial copper cable assemblies were developed to support SAS (Serial-Attached-SCSI) Enterprise storage networking links. These cables run at SAS 3Gb and 6G per lane and exceed SAS 2.1 requirements. These cables also support external SATA (Serial-Attached-ATA) storage networking requirements at 3Gb and 6Gb. Non-Equalized cables will perform at a maximum of 6Gb and Equalized a maximum of 3Gb. The SFF-8088 connectors feature low profile backshell enables easy access and removal in tight fitting areas. Applications include links for Drive to Host Controller Adapter, Host Controller Adapter to Switch and SAS Switch to Switch.

## Features & Benefits

Designed for 3Gb and 6G networking and exceed SAS 2.1 requirement

Connectors feature low profile backshell, enabling easy access and removal in tight fitting areas

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120061762	Country Of Origin	Taiwan, Province Of China
Application Sector	Commercial, Industrial	Warranty Type	Lifetime
Type	Cable		

### Dimensions

Cable Length	3.3 ft
--------------	--------

### Technical Information

Jacket Rating	Standard / Non-Rated	Cable Diameter	9.8 mm
---------------	----------------------	----------------	--------