



Cost-effective solution that provides higher bandwidth and transmission rates and supports longer distances with lower loss than 62.5/125 fiber. Specifically designed for use with today's narrower aperture components, this cable is fully compatible with multimode applications. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 50/125 multimode fiber, immune to electrical interference.

## Features & Benefits

Designed to support gigabit ethernet, fibre channel, ATM, and internet protocol applications

Patented injection molding process for greater durability

Optically inspected and tested for insertion loss

Pull-proof jacket design, immune to electrical interference

## Specifications

### General Info

|                    |                        |                   |           |
|--------------------|------------------------|-------------------|-----------|
| Product Line       | C2G                    | Color             | Orange    |
| UPC Number         | 757120110446           | Country Of Origin | Hong Kong |
| Application Sector | Commercial, Industrial | Type              | Cable     |

### Dimensions

|                   |        |              |        |
|-------------------|--------|--------------|--------|
| Product Length US | 9.8 FT | Cable Length | 9.8 ft |
|-------------------|--------|--------------|--------|

### Trade Programs

|               |     |
|---------------|-----|
| TAA Compliant | Yes |
|---------------|-----|

### Technical Information

|                        |                |                 |                          |
|------------------------|----------------|-----------------|--------------------------|
| Fiber Optic Cable Type | Multimode, OM2 | Jacket Material | PVC (Polyvinyl Chloride) |
| Bend Radius            | 45 mm          | Simplex/Duplex  | Duplex                   |
| Cable Type             | Fiber Optic    | Jacket Rating   | Standard / Non-Rated     |
| Data Transfer Rate     | 10 Gbps        | Connector 2     | SC Male                  |

---

|             |         |            |        |
|-------------|---------|------------|--------|
| Connector 1 | LC Male | Fiber Size | 50/125 |
|-------------|---------|------------|--------|

---