



Cost-effective solution that provides higher bandwidth and transmission rates and supports longer distances with lower loss than 62.5/125 fiber. Specifically designed for use with today's narrower aperture components, this cable is fully compatible with multimode applications. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 50/125 multimode fiber, immune to electrical interference.

Features & Benefits

Designed to support gigabit ethernet, fibre channel, ATM, and internet protocol applications

Optically inspected and tested for insertion loss

Patented injection molding process for greater durability

Pull-proof jacket design, immune to electrical interference

Specifications

General Info

| | | | |
|--------------------|------------------------|-------------------|-----------|
| Product Line | C2G | Color | Orange |
| UPC Number | 757120110637 | Country Of Origin | Hong Kong |
| Application Sector | Commercial, Industrial | Type | Cable |

Dimensions

| | |
|--------------|-------|
| Cable Length | 33 ft |
|--------------|-------|

Additional Information

| | | | |
|--------------------------|-----|--------------------------|------------------------------|
| Prop 65 Warning Required | Yes | Prop 65 Warning Language | Cancer and Reproductive Harm |
|--------------------------|-----|--------------------------|------------------------------|

Technical Information

| | | | |
|--------------------|----------------|-----------------|--------------------------|
| Cable Type | Multimode, OM2 | Jacket Material | PVC (Polyvinyl Chloride) |
| Bend Radius | 45 mm | Simplex/Duplex | Duplex |
| Cable Type | Fiber Optic | Jacket Rating | Standard Non-Rated |
| Data Transfer Rate | 10 Gbps | Adapter Rear | ST Male |
| Adapter Front | LC Male | Fiber Size | 50/125 |