



For voice/data/video distribution, this cable will handle bandwidth-intensive applications. Meets all Cat5E TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL) . Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality cable and a shortened body plug, this design minimizes Near-End Crosstalk (NEXT) levels.

Please Note: Solid Cat5E patch cables offer increased performance for "over Cat5" signal boosters.

## Features & Benefits

Solid twisted pair cable for high performance networking applications

Supports 1 Gigabit networks up to 328ft for fast data transmission and maximum performance

Meets all Cat5e TIA/EIA requirements for supporting a wide variety of applications

Designed to minimize Near-End Crosstalk (NEXT) levels

## Specifications

### General Info

Product Line	C2G	Color	Blue
UPC Number	757120151616	Country Of Origin	Vietnam
Features	Solid Conductors	Application Sector	Commercial, Industrial, Residential
Type	Cable		

### Dimensions

Product Length US	25.0 FT	Cable Length	25 ft
Outside Diameter	5.5 mm		

### Listing Agencies / 3rd Party Agencies

CE Certified	Yes	REACH Compliant	Yes
--------------	-----	-----------------	-----

### Additional Information

RoHS Compliant	Yes
----------------	-----

---

## Technical Information

---

Jacket Material	PVC (Polyvinyl Chloride)	Category Performance Rating	Cat 5e
Wire Gauge	24 AWG	Shielded/Unshielded	Unshielded
Conductor	4-Pair Twisted	Shield Type	UTP
Cable Type	Ethernet Patch Cable	Jacket Rating	Standard / Non-Rated
Connector Type	Booted	Indoor/Outdoor	Indoor
Connector 2	RJ-45 Male	Connector 1	RJ-45 Male
Operating Temperature	-20°-80°C	Insulation Material	HDPE (High-density Polyethylene)
Storage Temperature	-20° - 80° C		

---