



The DisplayPort Female to Female Panel Mount Coupler is the perfect solution for combining two DisplayPort cables to achieve connectivity through a panel. This allows the user to provide display connectivity from a source that is contained within a secure location. The coupler is compact and designed for minimal signal loss. The passive design of this coupler allows it to support video resolutions of up to 1080p.

Note: Standard signal length limitations apply to coupled cables

Features & Benefits

Support video resolutions of up to 1080p

Allows two DisplayPort cables to achieve connectivity through a panel

Compact and designed for minimal signal loss

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120184058	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Coupler		

Dimensions

Product Width US	1.08 in	Product Height US	0.48 in
Product Length US	1.58 in		

Technical Information

Video Resolution	1080p	Storage Humidity	15-85% RH (Non-Condensing)
Connector 2	DisplayPort Female	Connector 1	DisplayPort Female

Video Output Support	DisplayPort	Operating Temperature	0°-50°C
----------------------	-------------	-----------------------	---------

Operating Humidity	15-85% RH (Non-Condensing)	Video Input Support	DisplayPort
--------------------	----------------------------	---------------------	-------------

Storage Temperature	-25° - 85° C
---------------------	--------------
