For fast Ethernet computer networks that require bandwidth-intensive voice, data, or video distribution applications. Meets all Cat5e TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code your network installation.

Features & Benefits

Designed for network adapters, hubs, switches, routers, HDBaseT Supports 1 Gigabit networks up to 328ft for fast data transmission and applications and more

maximum performance

of applications

Meets all Cat5e TIA/EIA requirements for supporting a wide variety Constructed with unshielded twisted pair (UTP) wires, designed to counter EMI, RFI, and crosstalk

CMG rated jacket for in-wall installations

Specifications

General Info			
Product Line	C2G	Replaced by Part Number	29032
Color	Gray	UPC Number	757120243533
Country Of Origin	China	Application Sector	Commercial, Industrial, Residential
Туре	Cable		
Dimensions			
Cable Length	7 ft	Outside Diameter	5.2 mm
Technical Information			
Jacket Material	PVC (Polyvinyl Chloride)	Category Performance Rating	Cat5e
Wire Gauge	24 AWG	Shielded/Unshielded	Unshielded
Conductor	4-Pair Twisted	Shield Type	UTP
Cable Type	Ethernet Patch Cable	Jacket Rating	Standard / Non-Rated
Connector Type	Non-booted	Indoor/Outdoor	Indoor
Connector 2	RJ-45 Male	Connector 1	RJ-45 Male
Bandwidth	350 mHz	Insulation Material	HDPE (High-density Polyethylene)