

For fast Ethernet computer networks that require bandwidth-intensive voice, data, or video distribution applications. Meets all Cat5e TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code your network installation.

## Features & Benefits

Designed for network adapters, hubs, switches, routers, HDBaseT<br/>applications and moreSupports 1 Gigabit networks up to 328ft for fast data transmission and<br/>maximum performanceMeets all Cat5e TIA/EIA requirements for supporting a wide variety<br/>of applicationsConstructed with unshielded twisted pair (UTP) wires, designed to counter<br/>EMI, RFI, and crosstalk

CMG rated jacket for in-wall installations

## Specifications

## General Info

Product Line	C2G	Replaced by Part Number	29033
Color	Gray	UPC Number	757120243540
Country Of Origin	China	Application Sector	Commercial, Industrial, Residential
Туре	Cable		
Dimensions			
Cable Length	7 ft	Outside Diameter	5.2 mm
Technical Information			
Jacket Material	PVC (Polyvinyl Chloride)	Category Performance Rating	Cat5e
Wire Gauge	24 AWG	Shielded/Unshielded	Unshielded
Conductor	4-Pair Twisted	Shield Type	UTP
Cable Type	Ethernet Patch Cable	Jacket Rating	Standard / Non-Rated
Connector Type	Non-booted	Indoor/Outdoor	Indoor
Connector 2	RJ-45 Male	Connector 1	RJ-45 Male
Bandwidth	350 mHz	Insulation Material	HDPE (High-density Polyethylene)