

C2G

Discontinued - 3ft (0.9m) Cat5e Non-Booted Unshielded (UTP) Network Crossover Patch Cable - Gray

Part No. CG-24490



This Cat5e network crossover patch cable is an ideal solution for connecting two computer to share files or data. The crossed pin configuration allows two computers to be connected peer-to-peer without the need for a hub or switch. This cable may also be used to connect network switches and hubs without an uplink port to other switches and hubs. This cable is constructed to meet all Cat5e TIA/EIA standards, and has been designed to drastically reduce both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality cable and a shortened body plug, this design minimizes Near-End Crosstalk (NEXT) levels.

Features & Benefits

Perfect for networking two PCs together

Available in 7 colors to color-code a network

Standard RJ45 connectors

Available in lengths up to 25ft

Specifications

| General Info | | | | |
|-----------------------|---------------------------------|--|----------------------------------|--|
| Product Line | C2G | Replaced by Part Number | 27821 | |
| Color | Gray | UPC Number | 757120244905 | |
| Country Of Origin | Vietnam | Application Sector Commercial, Industrial, Resid | | |
| Туре | Cable | | | |
| Dimensions | | | | |
| Cable Length | 3 ft | Outside Diameter | 5.3 mm | |
| Technical Information | | | | |
| Jacket Material | PVC (Polyvinyl Chloride) | Category Performance Rating | Cat5e | |
| Wire Gauge | 24 AWG | Shielded/Unshielded | Unshielded | |
| Conductor | 4-Pair Twisted | Shield Type | UTP | |
| Cable Type | Crossover, Ethernet Patch Cable | Jacket Rating | Standard / Non-Rated | |
| Cable Diameter | 5.3 mm | Connector Type | Non-booted | |
| Indoor/Outdoor | Indoor | Connector 2 | RJ-45 Male | |
| Connector 1 | RJ-45 Male | Bandwidth | 350 mHz | |
| Operating Temperature | -20°-80°C | Insulation Material | HDPE (High-density Polyethylene) | |

| -20° - 80° C | | -20° | _ | 80° | С |
|--------------|--|------|---|-----|---|
|--------------|--|------|---|-----|---|

Storage Temperature