



For fast Ethernet networks that require bandwidth-intensive voice, data, or video distribution applications. Meets all Cat5e TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code your network installation.

## Features & Benefits

Designed for network adapters, hubs, switches, routers and more

Available in 10 colors to color-code a network

CMG In-Wall Rated Jacket

Constructed with unshielded twisted pair wires

Available in lengths up to 150ft

## Specifications

### General Info

Product Line	C2G	Replaced by Part Number	04143
Color	Green	UPC Number	757120250388
Country Of Origin	China	Application Sector	Commercial, Industrial, Residential
Type	Cable		

### Dimensions

Cable Length	35 ft	Outside Diameter	5.3 mm
--------------	-------	------------------	--------

### Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Category Performance Rating	Cat 5e
Wire Gauge	24 AWG	Shielded/Unshielded	Unshielded
Conductor	4-Pair Twisted	Shield Type	UTP
Cable Type	Ethernet Patch Cable	Jacket Rating	Standard / Non-Rated
Cable Diameter	5.3 mm	Connector Type	Non-booted

---

Indoor/Outdoor	Indoor	Connector 2	RJ-45 Male
----------------	--------	-------------	------------

---

Connector 1	RJ-45 Male		
-------------	------------	--	--

---