



This PCI bus 8-port serial board, with a fan-out (octopus) cable, configures 8 COM ports on the faster PCI bus, at data rates up to 115.2 kbps. It is an extremely dependable communication solution for ISPs or any type of RAS system that does not deal with an overwhelming amount of traffic. Each port includes integrated 16-byte FIFO buffer with software-configurable Tx/Rx triggers.

All eight ports share one PCI bus IRQ, even when accessed simultaneously, and thus saves valuable resources for other expansion cards. The first four serial ports have all of the standard serial signals, while the the last four serial ports do not include the Ring Indicator (RI) input. With easy plug-and-play installation, the Lava Octopus-550 automatically selects the next available IRQ and COM address; just plug it in and go!

## Features & Benefits

- Allows for dependable communication for ISPs or any type of RAS system
- Allows for dependable communication for ISPs or any type of RAS system
- Allows for dependable communication for ISPs or any type of RAS system
- Allows for dependable communication for ISPs or any type of RAS system
- Allows for dependable communication for ISPs or any type of RAS system
- Allows for dependable communication for ISPs or any type of RAS system

## Specifications

### General Info

Product Line	C2G	UPC Number	757120268062
Country Of Origin	Canada	Application Sector	Residential, Commercial, Industrial
Type	Accessory		

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

### Technical Information

---

Adapter Front

DB9 Male, DB9 Male, DB9 Male, DB9  
Male, DB9 Male, DB9 Male, DB9 Male,  
DB9 Male

---