

This precision-engineered cable is fully compliant with the DVI standard defined by DDWG (Digital Display Working Group). The DVI-I single link configuration provides enough bandwidth for resolutions up to 1600 x 1200 pixels and allows high speed transmission up to 4.95 Gbps. Three analog 30 AWG coaxial lines enable high speed analog transmission.



Tri-shielded undermold and braid shield protects against unwanted EMI/RFI interference. Each coax line is individually wrapped in foam-polyolefin insulation and overwrapped with a braided tinned copper shield. 28 AWG copper conductors are individually insulated in hard-density polypropylene to minimize crosstalk, and ensure high speed, error-free transmission. Gold-plated contacts provide full conductivity with no data loss. PC and Mac compatible cable supports hot-plugging of DVI display devices. PC-99 color-coded: white.

Please Note: The DVI-I plug connector can only be inserted into a DVI-I interface.

Features & Benefits

- 18-pin cable supports digital and analog transmission up to 4.95 Gbps
- Perfect for connecting digital displays and projectors to a PC
- Available in lengths up to 5m

Specifications

General Info

Product Line	C2G	UPC Number	757120269465
Country Of Origin	China	Application Sector	Residential, Commercial
Type	Cable		

Dimensions

Cable Length	6.6 ft
--------------	--------

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	30 AWG
Video Resolution	UXGA (1600x1200)	Cable Type	Video
Jacket Rating	Standard Non-Rated	Data Transfer Rate	4.95 Gbps
Adapter Rear	DVI-I Single Link Male	Adapter Front	DVI-I Single Link Male
