



This precision-engineered cable is fully compliant with the DVI standard defined by DDWG (Digital Display Working Group). The DVI-I single link configuration provides enough bandwidth for resolutions up to 1600 x 1200 pixels and allows high speed transmission up to 4.95 Gbps. Three analog 30 AWG coaxial lines enable high speed analog transmission.

Tri-shielded undermold and braid shield protects against unwanted EMI/RFI interference. Each coax line is individually wrapped in foam-polyolefin insulation and overwrapped with a braided tinned copper shield. 28 AWG copper conductors are individually insulated in hard-density polypropylene to minimize crosstalk, and ensure high speed, error-free transmission. Gold-plated contacts provide full conductivity with no data loss. PC and Mac compatible cable supports hot-plugging of DVI display devices. PC-99 color-coded: white.

Please Note: The DVI-I plug connector can only be inserted into a DVI-I interface.

## Features & Benefits

18-pin cable supports digital and analog transmission up to 4.95 Gbps

Perfect for connecting digital displays and projectors to a PC

Available in lengths up to 5m

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120269472	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Cable

### Dimensions

Cable Length	9.8 ft
--------------	--------

### Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	30 AWG
Video Resolution	UXGA (1600x1200)	Cable Type	Video

---

Jacket Rating	Standard / Non-Rated	Data Transfer Rate	4.95 Gbps
Connector 2	DVI-I Single Link Male	Connector 1	DVI-I Single Link Male
Video Output Support	DVI-I	Video Input Support	DVI-I

---