



This precision-engineered cable is fully compliant with the DVI standard defined by DDWG (Digital Display Working Group). The DVI-I dual link configuration provides enough bandwidth for resolutions up to 2560 x 1600. Three analog 30 AWG coaxial lines enable high speed analog transmission.

Tri-shielded undermold and braid shield protects against unwanted EMI/RFI interference. Each coax line is individually wrapped in foam-polyolefin insulation and overwrapped with a braided tinned copper shield. 28 AWG copper conductors are individually insulated in hard-density polypropylene to minimize crosstalk, and ensure high speed, error-free transmission. Gold-plated contacts provide full conductivity with no data loss. PC and Mac compatible cable supports hot-plugging of DVI display devices. PC-99 color-coded: white.

Features & Benefits

24-pin cable supports digital and analog transmission

Perfect for connecting digital displays and projectors to a PC

Available in lengths up to 5m

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120269496	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Cable

Dimensions

Product Length US	9.8 FT	Cable Length	9.8 ft
-------------------	--------	--------------	--------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	30 AWG
Video Resolution	UXGA (1600x1200)	Cable Type	Video
Jacket Rating	Standard / Non-Rated	Connector 2	DVI-I Dual Link Male

Connector 1	DVI-I Dual Link Male	Video Output Support	DVI-I
Operating Temperature	-20°-80°C	Video Input Support	DVI-I
Storage Temperature	-20° - 80° C		
