

Digital Visual Interface (DVI) is the standard interface for high-performance connection between PCs and flat panel displays, CRT displays, projectors, and HDTV. This video cable is fully compliant with the DVI standard defined by DDWG (Digital Display Working Group). Three analog 30 AWG coaxial lines enable high speed analog transmission.



Tri-shielded undermold and braid shield protects against unwanted EMI/RFI interference. Each coax line is individually wrapped in foam-polyolefin insulation and overwrapped with a braided tinned copper shield. 28 AWG copper conductors are individually insulated in hard-density polypropylene to minimize crosstalk, and ensure high speed, error-free transmission. Gold-plated contacts provide full conductivity with no data loss. PC and Mac compatible cable supports hot-plugging of DVI display devices. PC-99 color-coded: blue, white.

Please Note: The DVI connector on this cable can only be inserted into a DVI-I interface.

Features & Benefits

- Perfect for connecting VGA devices to analog DVI Displays
- Supports resolutions up to 1600 x 1200
- Use with DVI-I port on display
- Available in lengths up to 5m

Specifications

General Info

Product Line	C2G	UPC Number	757120269557
Country Of Origin	China	Application Sector	Residential, Commercial
Type	Cable		

Dimensions

Cable Length	9.8 ft
--------------	--------

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	30 AWG
Video Resolution	UXGA (1600x1200)	Cable Type	Video
Jacket Rating	Standard Non-Rated	Adapter Rear	VGA Male
Adapter Front	DVI-A Male		
