



This Cat5e shielded network patch cable is an ideal solution for making a network connecting in a noisy, EMI/RFI, environment. The F/UTP shielding features an overall cable shield which provides protection from EMI/RFI noise and electromagnetic interference. This cable meets or exceeds industry standards for NEXT and return loss. The molded boot provides extra strain relief and durability. Available in a variety of colors to easily color-code your network installation.

Please Note: For maximum protection against EMI/RFI interference, use our Cat5E shielded patch panel (#03864) and Cat5E shielded keystone jacks for complete end-to-end protection.

Features & Benefits

- Designed for network adapters, hubs, switches, routers, HDBaseT applications and more
- Supports 1 Gigabit networks up to 328ft for fast data transmission and maximum performance
- Meets all Cat5e TIA/EIA requirements for supporting a wide variety of applications
- Constructed with shielded twisted pair (STP) wires, designed to protect a high speed network from noise and electromagnetic interference
- Snagless connector design for high density environments and protecting the RJ-45 connector's lock
- Available in a variety of colors to color-code a network

Specifications

General Info

Product Line	C2G	Replaced by Part Number	00831
Color	Green	UPC Number	757120272540
Country Of Origin	China	Application Sector	Commercial, Industrial, Residential
Type	Cable		

Dimensions

Cable Length	7 ft	Outside Diameter	6 mm
--------------	------	------------------	------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Category Performance Rating	Cat 5e
Wire Gauge	24 AWG	Shielded/Unshielded	Shielded
Conductor	4-Pair Twisted	Shield Type	STP
Cable Type	Ethernet Patch Cable	Jacket Rating	Standard / Non-Rated
Cable Diameter	6 mm	Connector Type	Booted, Snagless

Indoor/Outdoor	Indoor	Connector 2	RJ-45 Male
Connector 1	RJ-45 Male	Operating Temperature	-20°-80°C
Insulation Material	HDPE (High-density Polyethylene)	Storage Temperature	-20° - 80° C
