



Digital Visual Interface (DVI) is the standard interface for high-performance connection between PCs and flat panel displays, CRT displays, projectors, and HDTV. This video cable is fully compliant with the DVI standard defined by DDWG (Digital Display Working Group). Three analog 30 AWG coaxial lines enable high speed analog transmission.

Tri-shielded undermold and braid shield protects against unwanted EMI/RFI interference. Each coax line is individually wrapped in foam-polyolefin insulation and overwrapped with a braided tinned copper shield. 28 AWG copper conductors are individually insulated in hard-density polypropylene to minimize crosstalk, and ensure high speed, error-free transmission. Gold-plated contacts provide full conductivity with no data loss. PC and Mac compatible cable supports hot-plugging of DVI display devices. PC-99 color-coded: blue, white.

Please Note: This DVI-A connector is compatible with a DVI-I port only and not a DVI-D port.

Features & Benefits

- Connect to an existing VGA cable for extra distance to a DVI monitor
- Tri-shielded for use in high EMI environments
- Available in lengths up to 7.5m

Specifications

General Info

Product Line	C2G	Application Sector	Residential, Commercial
Type	Cable		

Dimensions

Cable Length	9.8 ft
--------------	--------

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Video Resolution	QXGA (2048x1536)
Cable Type	Extension, Video	Jacket Rating	Standard Non-Rated

Adapter Rear

VGA Female

Adapter Front

DVI-A Male
