



This Cat5e shielded network patch cable is an ideal solution for making a network connecting in a noisy, EMI/RFI, environment. The F/UTP shielding features an overall cable shield which provides protection from EMI/RFI noise and electromagnetic interference. This cable meets or exceeds industry standards for NEXT and return loss. The molded boot provides extra strain relief and durability. Available in a variety of colors to easily color-code your network installation.

Please Note: For maximum protection against EMI/RFI interference, use our Cat5E shielded patch panel (#03864) and Cat5E shielded keystone jacks for complete end-to-end protection.

Features & Benefits

| | |
|---|--|
| Designed for network adapters, hubs, switches, routers, HDBaseT applications and more | Supports 1 Gigabit networks up to 328ft for fast data transmission and maximum performance |
| Meets all Cat5e TIA/EIA requirements for supporting a wide variety of applications | Constructed with shielded twisted pair (STP) wires, designed to protect a high speed network from noise and electromagnetic interference |
| Snagless connector design for high density environments and protecting the RJ-45 connector's lock | Available in a variety of colors to color-code a network |

Specifications

General Info

| | | | |
|--------------------|-------------------------------------|-------------------|--------|
| Product Line | C2G | Color | Yellow |
| UPC Number | 757120287032 | Country Of Origin | China |
| Application Sector | Commercial, Industrial, Residential | Type | Cable |

Dimensions

| | | | |
|--------------|-------|------------------|------|
| Cable Length | 75 ft | Outside Diameter | 6 mm |
|--------------|-------|------------------|------|

Technical Information

| | | | |
|-----------------|--------------------------|-----------------------------|----------------------|
| Jacket Material | PVC (Polyvinyl Chloride) | Category Performance Rating | Cat 5e |
| Wire Gauge | 24 AWG | Shielded/Unshielded | Shielded |
| Conductor | 4-Pair Twisted | Shield Type | STP |
| Cable Type | Ethernet Patch Cable | Jacket Rating | Standard / Non-Rated |
| Cable Diameter | 6 mm | Connector Type | Booted, Snagless |
| Indoor/Outdoor | Indoor | Connector 2 | RJ-45 Male |

| | | | |
|-------------|------------|-----------------------|-----------|
| Connector 1 | RJ-45 Male | Operating Temperature | -20°-80°C |
|-------------|------------|-----------------------|-----------|

| | | | |
|---------------------|----------------------------------|---------------------|--------------|
| Insulation Material | HDPE (High-density Polyethylene) | Storage Temperature | -20° - 80° C |
|---------------------|----------------------------------|---------------------|--------------|
