



C2G

Discontinued - 100ft (30.5m) Cat5e Snagless Shielded (STP) Ethernet Network Patch Cable - Yellow

Part No. CG-28709



This Cat5e shielded network patch cable is an ideal solution for making a network connecting in a noisy, EMI/RFI, environment. The F/UTP shielding features an overall cable shield which provides protection from EMI/RFI noise and electromagnetic interference. This cable meets or exceeds industry standards for NEXT and return loss. The molded boot provides extra strain relief and durability. Available in a variety of colors to easily color-code your network installation.

Please Note: For maximum protection against EMI/RFI interference, use our Cat5E shielded patch panel (#03864) and Cat5E shielded keystone jacks for complete end-to-end protection.

Features & Benefits

Designed for network adapters, hubs, switches, routers, HDBaseT applications and more

Supports 1 Gigabit networks up to 328ft for fast data transmission and maximum performance

Meets all Cat5e TIA/EIA requirements for supporting a wide variety of applications

Constructed with shielded twisted pair (STP) wires, designed to protect a high speed network from noise and electromagnetic interference

Snagless connector design for high density environments and protecting the RJ-45 connector's lock

Available in a variety of colors to color-code a network

Specifications

General Info

Product Line	C2G	Color	Yellow
UPC Number	757120287094	Country Of Origin	China
Application Sector	Commercial, Industrial, Residential	Type	Cable

Dimensions

Cable Length	100 ft	Outside Diameter	6 mm
--------------	--------	------------------	------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Category Performance Rating	Cat 5e
Wire Gauge	24 AWG	Shielded/Unshielded	Shielded
Conductor	4-Pair Twisted	Shield Type	STP
Cable Type	Ethernet Patch Cable	Jacket Rating	Standard / Non-Rated
Cable Diameter	6 mm	Connector Type	Booted, Snagless
Indoor/Outdoor	Indoor	Connector 2	RJ-45 Male

Connector 1	RJ-45 Male	Operating Temperature	-20°-80°C
-------------	------------	-----------------------	-----------

Insulation Material	HDPE (High-density Polyethylene)	Storage Temperature	-20° - 80° C
---------------------	----------------------------------	---------------------	--------------
