



Enables data transmission up to 10 times faster than an ordinary phone cable when connecting telephones, answering machines, and fax machines. Ultra-flexible jacket makes cable installation easy. 24k gold-plated connectors provide corrosion resistance for maximum conductivity. Snagless, molded connector enables increased flexibility and durability for effective strain relief.

Foil double-shielding with the braid shield reduce interference while the twisted-pair construction minimizes crosstalk for high speed, error-free data transfer.

Features & Benefits

Use to connect a modem to a telephone jack
 Double foil shielded to reduce EMI

Standard RJ11 telephone connectors
 Available in lengths up to 100ft

Specifications

General Info

| | | | |
|-------------------|----------|--------------------|-------------------------------------|
| Product Line | C2G | UPC Number | 757120287223 |
| Country Of Origin | Vietnam | Application Sector | Commercial, Industrial, Residential |
| Warranty Type | Lifetime | Type | Cable |

Dimensions

| | | | |
|-------------------|---------|--------------|-------|
| Product Length US | 15.0 FT | Cable Length | 15 ft |
| Outside Diameter | 5.5 mm | | |

Listing Agencies / 3rd Party Agencies

| | | | |
|--------------|-----|-----------------|-----|
| CE Certified | Yes | REACH Compliant | Yes |
|--------------|-----|-----------------|-----|

Additional Information

RoHS Compliant Yes

Technical Information

Jacket Material PVC (Polyvinyl Chloride) Wire Gauge 24 AWG

Cable Type Modem Jacket Rating Standard / Non-Rated

Indoor/Outdoor Indoor Connector 2 RJ-11 Male

Connector 1 RJ-11 Male Operating Temperature -20°-80°C

Storage Temperature -20° - 80° C
