



This USB 2.0 USB-C to USB-Mini B cable is the perfect solution for connecting a camera, cellphone, tablet or other device that has a USB Mini B port to a computer, tablet or other device that has a USB Type-C port for USB 2.0 communication. The color coded USB Type-C connector allows this cable to be easily identified as a USB 2.0 cable and differentiated from other cables which may support a different feature set. The USB Type-C connector is smaller than traditional USB connector and features a symmetrical design which allows it to be easily connected on the first try. Additionally, the durability of the USB Type-C connector allows for up to 10,000 connection cycles. This cable supports a data rate up to 480Mbps for data transfer and sync with 5 volts and 1 amp of power for device operation and charging.

Note: This cable is designed to support USB 2.0 communication and features and is not able to support USB 3.1 Gen 2 Communication and features.

Learn more about the new [USB 3.1 Specification and new USB Type-C Connector](#).

Features & Benefits

Connect the USB-Mini B port of a camera, cellphone, tablet or other device to a Type-C port

Designed to support USB 2.0 communication and features

Backwards compatible with USB 2.0 and USB 1.1 devices

Color coded white and labeled to designate USB 2.0 feature support

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120288558	Country Of Origin	Vietnam
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Cable		

Dimensions

Product Length US	6.0 FT	Cable Length	6 ft
-------------------	--------	--------------	------

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	FCC Compliant	Yes
--------------	-----	---------------	-----

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	30 AWG
Storage Humidity	0-90% RH	Conductor Stranding	Stranded
Signal Transmission	Bidirectional	Cable Type	USB
Amperage	1 A	Cable Diameter	3.8 mm
Data Transfer Rate	480 Mbps	Connector 2	USB Mini-B Male
Connector 1	USB-C Male	Operating Temperature	0°-50°C
Operating Humidity	20-85% RH	Storage Temperature	-25° - 70° C
