



Improve the performance of your progressive scan video sources by providing a much better cable than "out of the box" cables included with most consumer electronics products. The oxygen-free copper center conductor and foam PE dielectric maintain a 75 Ohm characteristic impedance, and offer efficient signal transmission to deliver exceptional video detail, color and brightness.

The dual braided oxygen-free copper shields and 100% aluminum foil sheath protect against environmental noise and interference. The 24K gold-plated, heavy duty connectors ensure long-lasting, highly conductive signal connections; fully molded connectors provide excellent strain relief. The color-coded molded connectors attach to an ultra-flexible jacket, and enable easy installation and identification.

## Features & Benefits

Carries a Component Video signal

Constructed from 75oxygen-free copper

Foil and braided shield to protect from interference

## Specifications

### General Info

Product Line	C2G	UPC Number	757120291138
Country Of Origin	China	Application Sector	Residential, Commercial
Type	Cable		

### Dimensions

Cable Length	50 ft
--------------	-------

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

### Technical Information

Cable Type	Video	Adapter Rear	RCA Component Video Male
Adapter Front	RCA Component Video Male		