



A cable whose job is to transmit just two or three octaves of audio information enjoys the most relaxed requirements of any interconnects in the system. Or does it? Long lengths, punishing environmental factors and the necessity to handle extreme dynamic range are all part of the subwoofer interconnect's job description. This subwoofer cable offers superb impact and detail while maintaining a "tough as nails" built quality!

Twisted pair oxygen-free copper wire and foamed PE dielectric fight noise and hum, and are optimized for bass signal transmission. Oxygen-free copper conductors deliver awesome impact and bass detail. The low loss 100% foil and spiral-wound oxygen-free copper (OFC) shielding protects the important bass signals from electromagnetic interference (EMI) and radio frequency interference (RFI). A tough, ultra-flexible jacket and 24K gold-plated heavy duty contacts ensure a lifetime of performance.

Features & Benefits

Shielded to prevent unwanted EMI/RFI interference

Oxygen-free copper conductors

Ultra-flexible jacket

24K gold-plated heavy duty contacts

Specifications

General Info

Product Line	C2G	Color	Blue
UPC Number	757120291206	Country Of Origin	Vietnam
Application Sector	Commercial, Residential	Type	Cable

Dimensions

Cable Length	25 ft
--------------	-------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	24 AWG
Signal Transmission	Bidirectional	Cable Type	Audio
Jacket Rating	Standard / Non-Rated	Cable Diameter	5.15 mm

Connector 2

RCA Line-level Audio Male

Connector 1

RCA Line-level Audio Male
