



Connect digital camcorders, satellite receivers, DVD players, PC with TV out or any video source with s-video output jacks to a TV, monitor or a/v receiver with s-video input jacks. Our s-video cable also provides the right solution for connecting extended definition video recorders or digital satellite systems to your a/v receiver or television/monitor. Carefully designed precision video conductors ensure optimal video quality.

Individually shielded Y (luminance) and C (chrominance) conductors are combined with an overall aluminum foil and OFC braid shield to protect against radio frequency interference (RFI) and electromagnetic interference (EMI). This cost-effective high-performance cable ensures maximum video quality when compared with s-video cables typically included with consumer electronics products.

Oxygen-free copper wire and the 24K gold-plated OFC connectors deliver all the detail, color and brightness you expect from your s-video component. Fully molded connectors provide excellent strain relief while the stylish, ultra-flexible PVC jacket enhances cable durability for years of audio/video enjoyment.

Please Note: In addition to fitting standard 4-pin s-video jacks, the Velocity s-video cable fits most 7-pin jacks found on desktop and laptop PCs with a TV out jack.

Features & Benefits

Individually shielded conductors

Fully molded connectors

Flexible PVC jacket

24K gold plated connectors

Specifications

General Info

Product Line	C2G	Color	Blue
UPC Number	757120291626	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Cable

Dimensions

Cable Length	75 ft	Outside Diameter	7.1 mm
--------------	-------	------------------	--------

Technical Information

Wire Gauge	24 AWG	Storage Humidity	20-80% RH (Non-Condensing)
Cable Type	Video	Cable Diameter	7.1 mm
Connector 2	S-Video Male	Connector 1	S-Video Male
Operating Temperature	-20°-80°C	Storage Temperature	-20° - 80° C