



The HDMI® and VGA + Stereo Audio to HDMI HDBaseT over Cat Extender Kit is a complete solution for extending audio/video signals from a Blu-ray™ player and a laptop to the HDMI input of a projector. This kit extends HDMI, VGA and Stereo Audio signals over a single Cat5e, Cat6, or Cat6a network patch cable up to 230 feet at a 1080p resolution. The rear cable connections for the Cat cable and the optional serial cable are set at 90°, making connections in a wall box easy. The local HDMI output of the front of the wall plate allows an additional HDMI display to be supported via an HDMI cable. Switching between HDMI and VGA inputs is made easy with three options available. Automatic switching displays the last connected device, manual switching via the button on the front of the wall plate, or Serial RS232 switching which accepts serial commands from a control device, like our

## Features & Benefits

Perfect for extending audio/video signals from a Blu-ray™ player and a laptop to a projector

TruChoice™ power allows for power at the transmitter or receiver end

Utilizes a single Cat5e, Cat6 or Cat6a cable for extension

Kit includes both the transmitter and receiver units

Three methods for input switching: Auto, Manual, and Serial RS232

Compatible with any HDBaseT receiver from C2G

Designed for easy connections in a wall box

## Specifications

### General Info

Product Line	C2G	Color	White
UPC Number	757120292180	Country Of Origin	Taiwan, Province Of China
Application Sector	Commercial	Type	Active Device, Extender, HDBaseT, Kit

### Technical Information

Max Distance Support	230 ft	Video Resolution	1080p, 4K, 4K 30Hz
Storage Humidity	0-80% RH (Non-Condensing)	Number of Gangs	2
Operating Temperature	0°-40°C, 32°-104°F	Operating Humidity	0-80% RH (Non-Condensing)
Storage Temperature	-10° - 60° C, 14° - 140° F		