



This precision-engineered cable is fully compliant with the DVI standard defined by DDWG (Digital Display Working Group). The DVI-I dual link configuration provides enough bandwidth for resolutions up to 2048 x 1536 pixels and allows high speed transmission up to 9.9 Gbps. Three analog 30 AWG coaxial lines enable high speed analog transmission.

Tri-shielded undermold and braid shield protects against unwanted EMI/RFI interference. Each coax line is individually wrapped in foam-polyolefin insulation and overwrapped with a braided tinned copper shield. 28 AWG copper conductors are individually insulated in hard-density polypropylene to minimize crosstalk, and ensure high speed, error-free transmission. Gold-plated contacts provide full conductivity with no data loss. PC and Mac compatible cable supports hot-plugging of DVI display devices. PC-99 color-coded: white.

**Please Note:** The DVI-I plug connector can only be inserted into a DVI-I interface.

## Features & Benefits

- Connects to an existing DVI-I male cable for extra distance
- Available in lengths up to 3m
- Supports resolutions up to 2048x1536 at 9.9Gbps

## Specifications

### General Info

Product Line	C2G	UPC Number	757120293224
Country Of Origin	China	Application Sector	Residential, Commercial
Type	Cable		

### Dimensions

Cable Length	9.8 ft
--------------	--------

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

### Technical Information

---

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	30 AWG
Video Resolution	QXGA (2048x1536)	Cable Type	Extension, Video
Jacket Rating	Standard Non-Rated	Data Transfer Rate	9.9 Gbps
Adapter Rear	DVI-I Dual Link Female	Adapter Front	DVI-I Dual Link Male

---