

This adapter cable will connect an inkjet, laser or other parallel printer to a computer with an available USB-C port. Multiple adapters can be connected to multiple printers at the same time, eliminating the need for a switchbox. This adapter auto-negotiates hardware recognition for faster protocol setup, and is fully plug-and-play compatible. This adapter cable is a perfect accessory for Apple®, Microsoft® Surface®, and other leading laptops and tablets.



The USB-C connector has a robust design, allowing for the connector to be plugged in and un-plugged up to 10,000 times. The sturdy construction ensures that the product provides peace of mind and is built to stand up to the rigors the most demanding on-the-go life. The USB-C connector has a symmetrical design which is identical on both sides, so it does not matter if you plug it in upside-down or right-side-up. It will plug in the first time, every time while preventing damage to the connector port.

Discover more connectivity solutions for [Apple Products](#)

Discover more connectivity solutions for the [Microsoft Surface](#)

## Features & Benefits

Convert a printer or other device with parallel protocol into USB protocol	Plug and play no drivers required
Reversible, symmetrical USB-C connector	Gold plated USB TYPE C connector
Compatible with the Apple® MacBook®, MacBook Air®, and MacBook Pro®	Compatible with the Microsoft® Surface® Book 2 and Surface Go

## Specifications

### General Info

Product Line	C2G	UPC Number	757120294801
Country Of Origin	China	Application Sector	Commercial, Residential
Warranty Type	3-Year	Type	Active Device, Adapter, Cable

### Dimensions

Cable Length	6 ft	Outside Diameter	3.5 mm
--------------	------	------------------	--------

### Listing Agencies / 3rd Party Agencies

---

FCC Compliant	Yes
---------------	-----

---

### Technical Information

---

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	28 AWG
-----------------	--------------------------	------------	--------

---

Conductor Stranding	Stranded	Cable Type	Adapter, Parallel, USB
---------------------	----------	------------	------------------------

---

Cable Diameter	3.5 mm	Data Transfer Rate	480 Mbps
----------------	--------	--------------------	----------

---

Connector 2	DB25 Female	Connector 1	USB-C Male
-------------	-------------	-------------	------------

---

Operating Temperature	-10°-50°C	Storage Temperature	-10° - 60° C
-----------------------	-----------	---------------------	--------------

---