



**C2G**  
**Discontinued - 2-Port UXGA Monitor Splitter/Extender (Male Input) (TAA Compliant)**  
Part No. CG-29550

Distribute any video signal to 2 different video outputs, while maintaining vivid picture quality. Though powerful, this splitter is easy to use; just connect the cables, and you're ready to go! There is no software required, or complicated interface cards to install. This monitor splitter not only distributes, but also boosts your high resolution video signal up to 210 feet.



Includes power-saving mode, color-coded connectors for the input and outputs, durable all-metal housing, power and activity LED indicators. Also suitable for XGA, SVGA, VGA, and MultiSync® resolution monitors. Daisy-chain multiple units together for even more outputs.

Please Note: The term "extender" refers to the product's ability to extend the distance of your cable runs to 210 feet. It does not mean the product provides "extended desktop" functionality, or the ability to view different information on each of your monitors. If you are looking to add extended desktop capabilities to your computer, please consider product #30534, 6in USB 2.0 to XGA Adapter. UXGA provides a screen resolution of 1600 x 1200 pixels. Replacement power supply part number #98033.

## Features & Benefits

Split a single VGA signal from a PC to two or more displays  
Combine multiple splitters to display signal to even more displays

Available in 2, and 4-port versions

## Specifications

### General Info

Product Line	C2G	Replaced by Part Number	29551
Color	Black	UPC Number	757120295501
Country Of Origin	Taiwan, Province Of China	Application Sector	Commercial, Residential
Type	Active Device, Extender, Splitter		

### Dimensions

Product Width US	7.12 in	Product Height US	0.78 in
Product Length US	3.15 in		

### Trade Programs

TAA Compliant	Yes
---------------	-----

---

## Technical Information

---

Max Distance Support	210 ft	Video Resolution	SVGA (800x600), UXGA (1600x1200), VGA (640x480), XGA (1024x768)
Amperage	600 mA	Cable Diameter	5.5 mm
Connector 2	VGA Female, VGA Female	Connector 1	VGA Male
Video Output Support	VGA	Operating Temperature	0°-40°C, 32°-104°F
Operating Humidity	0-80% RH (Non-Condensing)	Video Input Support	VGA
Storage Temperature	-10° - 60° C, 14° - 140° F		

---