

C2G

Discontinued - 33in USB 2.0 to IDE or Serial ATA Drive Adapter CablePart No. CG-30504



Turn any IDE or SATA drive into a convenient external drive! Simply connect one IDE/ATAPI or SATA-based mass storage device through a USB port to easily transfer files from a computer or laptop, backup files or store large file archives on an external hard drive. The USB 2.0 interface enables easy installation with its plug-and-play design. The adapter supports all existing IDE/ATAPI devices such as lomega® Zip®, CD-ROM, CD-RW, DVD-ROM and IDE hard drives. Compatible with current drive sizes on the market such as 1 and 2 TB SATA and 750 GB IDE drives. This adapter cable is a perfect accessory for Microsoft® Surface® products and other leading laptops.

Because this adapter can handle all sizes and types of mass storage drives, it's a great solution for recovering personal files from IDE or SATA drives from computers that have had motherboard failures. Includes an integrated USB transceiver; supports USB Suspend/Resume and Remote Wakeup; and a 5 Volt (1 Ampere) power supply that supports both SATA power and standard 4-pin Molex (LP4) power connectors. Plus, the on/off switch on the power supply lets you shut off an attached drive without having to disconnect when not in use. (for 3.5in and 5.25in drives), 44-pin IDC Female (for 2.5in drives), 7-pin SATA Female (for SATA drives).

Discover more connectivity solutions for the Microsoft Surface

Features & Benefits

Perfect for recovering files from a failed motherboard

Easily connect any IDE or SATA drive using a USB port

Plug and play design provides for seemless file transfer

Compatible with the Microsoft® Surface® Book 2, Surface Pro 6, Surface Laptop 2, and other leading laptops

Specifications

General Info			
Product Line	C2G	Color	Black
UPC Number	757120305040	Country Of Origin	China
Application Sector	Commercial, Residential	Туре	Adapter, Cable
Dimensions			
Cable Length	2.75 ft		

Technical Information

Cable Type	Adapter, Serial, USB	Connector 2	44-pin IDC Female, 40-pin IDC Female, SATA 7-pin Female
Connector 1	USB-A Male		