



This riser rated OM3 laser-optimized multimode (LOMMF) MPO fiber array cable is ready for deployment in any multimode 50/125 MTP/MPO network. OM3 is fully backward-compatible with existing OM2 or OM1 systems. This multimode, MPO fiber cable is comprised of 12 fiber channels within each connector. This high density MPO fiber cable is pinned out in type B format and is comprised of 12 fiber channels within each connector which is perfect when space is limited and makes it possible to run a single cable that automatically terminates 12 fibers in one easy plug-in. The push-pull release mechanism for the MPO connector is easy to engage and disengage, its latch design also prevents the plug from snagging when jumper cables are being routed.

Features & Benefits

- Type B pinout
- The MPO connector has a push pull spring loaded release
- 3mm jacket outer diameter
- No guide pins on either MPO connector
- Riser rated (OFNR) Jacket

Specifications

General Info

Product Line	C2G	UPC Number	757120313113
Country Of Origin	Hong Kong	Type	Cable

Dimensions

Cable Length	33 ft
--------------	-------

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Cable Type	Multimode, OM3, MPO, MTP	Jacket Material	PVC (Polyvinyl Chloride)
------------	--------------------------	-----------------	--------------------------